



Fire Prevention and Safety



Kitchen Fire

Suppression

Kitchen Exhaust Hood Cleaning



Grease Interceptors

200 - 100 Park Royal, West Vancouver, BC V7T 1A2

**Essential Commercial Kitchen Services** 

Bill TO:

**Dummy Company** 

c/o: Alex Collins test

,

Invoice: 58113

Date: 2023-07-19 Due Date:

Terms:

reims.

Service Report:

PO: Verbal REP: AC

**Products / Services** 

QTY.	COST	SKU	ITEM	DISCOUNT	TOTAL
1	\$0	1007016	1-115/208-230-1800 ODP 56H GP 1PH Res CS		\$0.00

GST: 747314888 **NET:** 

SUBTOTAL: \$0.00

GST 5%: \$0.00

\$0.00

**TOTAL:** \$0.00

Grease Ducks Ltd.

200 - 100 Park Royal

West Vancouver, BC V7T 1A2

Telephone: (604) 628-8881 Toll Free: 1-877-646-0887 service@greaseducks.com www.greaseducks.com Fire Prevention & Safety
Kitchen Exhaust Hood Cleaning
Fire Suppression Systems
Grease Interceptors

## **INSTALLATION BY OTHERS**

INSTALLATION BY OTHERS Field notes: Installation, ductwork, patching, all electrical field wiring, start-up & balance, gas or electric shutdown for fire system hook-up fire system hook-up, fire system chemical agent, NO2 cartridge, field piping, detection and pull station line(s), tests and permits.

Note: Customer is responsible for additional labor charges as a result of cooking equipment layout changes after the release of the order, union labor or prevailing wage charges, or additional trips by fire system distributor caused by jobsite delays, permits, fees or test required by local authority. Submittal will specify applicable testing and approval agencies. The fire suppression system final hook up is not included on this quote. The final hook up usually consists of, but is not limited to, the chemical agent, Wet chemical cylinder, field piping/repiping, detection and pull station line(s), tests, and permits. Hook up for the fire system must be performed by an Authorized Distributor. If not installed by an Authorized Distributor, then the warranty on this product will be voided.

**Grease Ducks Ltd. requirement for all field hook ups:** All fire system detection conduit must be half inch EMT. All conduit fittings must be compression type and fully tightened. All conduit ends must be reamed and deburred and blown clear of debris prior to assembly. All conduit must be fully and robustly supported to avoid accidental fire system discharge.

Ventilation Direct product must be installed in accordance with installation instructions provided with equipment or available on our web site at www.greaseducks.com.

## **SHIPPING**

Freight includes one shipment only, delivered to the job site address listed on this proposal. Customer is responsible for freight charges on any items shipped early. This is an estimated freight charge and is subject to change based on current freight costs when the job is released for production.

## **APPROVAL**

The above prices, specifications, and conditions are satisfactory and are hereby accepted. You are authorized to perform the
work specified. Receipt of the Grease Ducks Ltd. Terms & Conditions are hereby acknowledged and by signature hereto, we
agree to said Terms & Conditions. Payment will be made in accordance with authorized agreement. Please note, proposal may be withdrawn by Grease Ducks Ltd. if not accepted within 30 days.
2022 07 10

Date	
Date	
	Date

We accept MasterCard®, VISA® cards for immediate credit approval and expedited order processing.